

1.4 Supplier Information

Carlstadt, NJ 07072

Fax:

Phone: 201-438-7333

David Weber Oil Company 601 Industrial Road

201-438-3178 Email: sales@weberoil.com

Identification Section 1

1.1 Product Identifiers

Product Name

: Gibraltar Super S-3 Series

1.2 Product usage

Recommended Usage : engine Oil Restricted Usage : Not intended for any other usage

1.3 Emergency support

Emergency Support : CHEMTREC United States +1(800) 424-9300 International +01(703) 527-3887

Section 2- Composition/ Information on Ingredients

2.1 Classification of Substance Mixture

: No Classified Hazards GHS Rating(s) Signal Word : Not Applicable

| 2.2 Label Elements | | No classified Hazards | |
|--------------------|--------------|---|--|
| Precautionary: | P201 P202 | Obtain Special Instructions Before Use. Do Not Handle Until All Safety Precautions Are Understood. Use Personal Protective equipment | |
| Response: | P308 | If Exposed Or Concerned: Get Medical Advice/attention. | |
| Storage: | P405 | Store Locked Up. | |
| Disposal: | P501 | Dispose of container according to regional regulations | |

2.3 Other Hazards

Hazards not otherwise : Avoid prolonged or repeated contact with motor oil. Use of good hygiene practices will reduce Classified (HNOC) the likelihood of potential health effects. When exposed wash areas with soap and water and lauder contaminated clothing.

3.1 Substance details

| Chemical Name | GHS | CAS# | %Weight |
|---|---------------|--|---------------------|
| BASE OIL SEVERELY REFINED LUBRICANT BASE OIL (PETROLEUM) PHOSPHORODITHIOIC ACID, MIXED O,O-BIS (1,3-DIMETHYLBUTYL AND ISOPROPYL) ESTER | S, ZINC SALTS | 64742-65-0 64742-54-7 84605-29-8 | 53.0 21.0 1.0 |

INERT The remaining percentage are not listed as Physical or Health Hazards (29 CFR 1910.1200)25.0Products containing mineral oil with less than 3% DMSO extract as measured by IP-346.25.0

Section 4 – First aid Measures

| 4.1 First aid measures | |
|--|---|
| Eye Contact | : Immediately flush eyes with plenty of water occasionally lifting the upper and lower eyelids. Check and remove any contact lenses. Continue to rinse for at least 20 minutes. Get Medical Attention. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth resuscitation. Maintain an open airway. Get medical attention if symptoms occur. |
| Ingestion | : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. get medical attention if symptoms occur. |
| 4.2 Symptoms & Effects | |
| To Physician Specific Treatment | : Treat symptomatically. Contact poison specialist if product has been ingested. : No specific Treatment. |
| 4.3 Medical attention | |
| Protection of first Aiders Note to Doctor | No action should be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration. |

5.1 Extinguishing Media

Suitable Media Unsuitable Media Specific hazards Arising from this product : CO2, Dry chemical, or Foam. Water can be used to cool and protect product. Do not use water jet as an extinguisher, it will spread the fire.

: When heated, hazardous gases may be released including: sulfur dioxide. A solid stream of water will spread the burning material. Material creates a special hazard because it floats on water This material creates a special hazard because because it floats on water. This material is harmful to aquatic life. Any fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

5.2 Firefighters Advice

Special protective equipment

: Fire Equipment Information: Fire-fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment

General Measures : No health affects expect from the cleanup of this material if contact can be avoided. Follow personal protect equipment recommendations found in section 8 of this SDS.

6.2 Environmental Precautions

Non-Emergency Personnel : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform authorities if the product has caused environmental pollution Water Polluting Material may be harmful to the environment if released in large quantities.

6.3 Materials & Methods to Contain and Cleanup

Reference Section 8 : Follow all protective equipment recommendations provided in Section 8.

Spill Control Measures : Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

Containment and Cleanup : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via licensed waste disposal contractor. Contaminated absorbent material may pose the same threat hazard as the spilled product.

8.2 Exposure Controls

| 7.1 Safe Handling | |
|----------------------------------|--|
| Personal Protective Equipment | : Put on appropriate personal protective equipment (see section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, keep lid tightly closed when not in use. Empty containers that retain product residue and can be hazardous. Do not reuse container. |
| 7.2 Safe Storage | |
| Required conditions | : Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. Store away from incompatible materials. See section 10 for incompatible materials. |
| 7.3 Specific End Use | |
| Designed Purpose | : This product is designed for use as a Engine Oil. |
| Section 8 - Expos | ure Control |

| 8.1 United States Exposure Limits Chemical Name | Occupational Exposure Limits | Value |
|--|------------------------------|--------|
| Distillates, petroleum, hydro treated heavy paraffinic | OSHA - PEL ACGIH - 40 TWA | 5mg/m3 |

| Engineering Controls | : Material should be handled in enclosed vessels and equipment, in which case general room ventilation should be sufficient. Local exhaust ventilation should be used at points where dust, mist, vapors or gases can escape into the room air. No special requirements under ordinary conditions of use and with adequate ventilation. |
|------------------------|---|
| Environmental Exposure | |
| Control | misting is generated. |
| Hygiene Measures | : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. |
| Eye / Face Protection | : If contact is likely, safety glasses with side shields are recommended. |
| Skin / Hand Protection | : Butyl rubber. Use nitrile or neoprene gloves. Use good industrial hygiene practices. In case of skin contact, wash hands and arms with soap and water. Use caution when opening manway covers of storage and transportation containers. 3-nitroaniline crystals may be present on the interior surface of these openings. 3-nitroaniline is toxic by dermal exposure. |
| Respiratory Protection | : Use a properly fitted air purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this a necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |

9.1 Information On Basic Physical and Chemical Properties

| Physical state Color Odor Odor threshold pH Freezing Point Boiling Point / Range Flash Point COC Evaporation rate: Upper Explosive Limits (% air) Lower Explosive Limits (% air) Flammability (solid, gas) Vapor pressure Vapor density (air=1) | : Liquid : B&C : Characteristic of Petroleum : No Data Available : No Data Available : No Data Available : 221C : No Data Available : No Tapplicable : <1 mm Hg : >1 |
|--|--|
| Relative Density Auto-ignition temperature Decomposition temperature Solubility in water Partition coefficient, n-octanol/water | : 0.86 : Not Determined : Not Determined : Negligible, 0-1% : No Data Available |
| | |

9.2 Other Information (Approximated - not to be used as typical values)

Viscosity @ 40C Viscosity @ 100C : 89 cst : 13 cst

Section 10 - Stability & Reactivity

10.1 Material Analysis

Reactivity Chemical stability Possibility of hazardous reactions

10.2 Environmental

Conditions to avoid

Incompatible materials Hazardous decomposition products : No Data Available.

- : Stable Under Normal Circumstances.
- : Hazardous polymerization will not occur.

: Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).

: Strong oxidizing agents.

: Carbon monoxide, smoke carbon monoxide, sulfur oxides, aldehydes, and other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present.

11.1 Toxicological Effects

| Ingestion Toxicity | : No hazard in normal industrial use. |
|------------------------------------|---|
| Skin Contact | : This material is likely to be slightly irritating to skin based on animal data. |
| Inhalation Toxicity Eye Contact | Can cause minor skin irritation, defatting, and dermatitis. Likely to be practically non-toxic based on animal data. Non-hazardous under Respiratory sensitization category. The material is likely to be moderately irritating to eyes based on animal data. No hazard in normal industrial use. |

Section 11- Toxicological Information Continued

| Sensitizer Mutagenicity | No data available to indicate product or components may be a skin sensitizer. No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic. |
|---|--|
| Carcinogenicity | : Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer. |
| Reproductive and | : No data available to indicate product or any components present at greater than 0.1% |
| Developmental Toxicity | may cause birth defects. |
| Specific target organ toxicity (single exposure) | : Non-hazardous under Specific Target Organ Systemic Toxicity Single Exposure category. |
| Specific target organ toxicity (repeated exposure) | : Non-hazardous under Specific Target Organ Systemic Toxicity Repeated Exposure category. |

Section 12 - Ecological Information

12.1 Aquatic Toxicity

Acute Aquatic ecotoxicity Chronic Aquatic ecotoxicity Persistence and degradability Bioaccumulative potential Mobility in soil Results of PBT and vPvB assessment Other adverse effects

- : Non-hazardous under Aquatic Acute Environment category.
- : Non-hazardous under Aquatic Chronic Environment category.
- : Biodegrades slowly.
- : Bioconcentration may occur.
- : This material is expected to have essentially no mobility in soil.
- : Not determined.
- : No data available.

13.1 Waste treatment

Waste treatment methods **Disposal Methods** Waste Disposal

: Dispose of according to Federal, State, Local, or Provincial regulations.

: Recycle used oil.

: Spent or discarded material is non-hazardous according to environmental regulations.

Contaminated packaging

: Recycle containers whenever possible!

Section – 14 Transportation Information

14.1 U.S. Department of Transportation (DOT) **Shipping Description** : If shipped by land in a packaging having a capacity of 3,500 gallons or more, the provisions of 49 CFR, Part 130 apply. (Contains oil) International Maritime Dangerous Goods (IMDG) **DOT Compliance Note** : U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 25. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable International Civil Aviation Org. / International Air Transport Assoc. (ICAO/IATA) : U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 24

DOT Compliance Requirement

Section 15 - Regulatory Information

| Regulatory Agency | | Chemical List Status |
|--|---|----------------------------|
| (TSCA) Toxic WHMIS Hazard Class | : All components are either listed or not regulated US TSCA Inventory. : None | 64742-54-7 |
| Canada CPR | : This product has been classified in accordance with the hazard criteria Contr (CPR) and the SDS contains all the information required by the Regulations. | olled Products Regulations |
| CERCLA Sections 302, 313, 372 311, 312 | : This material does not contain reportable chemicals. : Acute Health Hazard No Pressure Hazard No Fire Hazard No Chronic Health Hazard No Reactive Hazard No | |
| New Jersey Right to Know (NJ RTK) | : This material does not contain reportable chemicals. | |
| Massachusetts Right to Know (MA RTK) | : This material does not contain reportable chemicals. | |
| Pennsylvania Right to Know (PA RTK) | : This material does not contain reportable chemicals. | |
| Rhode Island Right to Know (RI RTK) | : This material does not contain reportable chemicals. | |

| ACGIH CFR DOT GHS OSHA PEL RTK SARA TSCA WHMIS | American Conference of Governmental Industrial Hygienists Code of Federal Regulations United States Department of Transportation Globally Harmonized System of Classification and Labeling of Chemicals Occupational Safety and Health Administration Permissible Exposure Limit Right-to-Know Short-term Exposure Limit Toxic Substances Control Act Workplace Hazardous Materials Information System | NFPA: | HEALTH FLAMMABILITY INSTABILITY SPECIAL | 0 1 0 - |
|---|---|-------|--|------------------|
| WHMIS | Workplace Hazardous Materials Information System | | | |

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness.

Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.