

DAVID WEBER OIL CO.

601 Industrial Road - Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax www.weberoil.com

Section 1 – Identification

1.1 Product identifier

1.4 Supplier Information

Product Name : Permanent Anti-Freeze HD

David Weber Oil Co. 601 Industrial Road Carlstadt, NJ 07072

Manufactured By David Weber Oil Co.

1.2 Product usage

Recommended Usage

: Antifreeze Fluid

Restricted Usage

: Dilution to 50% is generally recommended: dilute to meet local condition.

1.3 Emergency support

Emergency Support : CHEMTREC

United States +1(800) 424-9300 International +01(703) 527-3887

Section 2- Hazards Identification

2.1 Hazard Classification

Acute Toxicity, Oral, Category 4
Skin Corrosion / Irritation, Category 2
Serious Eye Damage / Eye Irritation, Category 2A
Sensitization – Skin, Category 1
Toxic to Reproduction, Category 2
Specific Target Organ Toxicity (Single Exposure), Category 1
Pictogram Description GHS: Health Hazard, Exclamation Point

2.2 Hazard Statement

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility of the unborn child. Caused damage to the central nervous system (CNS) and kidneys if swallowed.

2.4 Other Hazards

Precautionary Statement: Prevention: Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wash hands and any other contaminated skin after handling. Do not eat, drink or smoke when using this product. Wear eye protection (splash goggles or full face shield), protective gloves and protective clothing (chemically impervious). Do not breathe

mist or spray. Contaminated work clothing must not be allowed out of the workplace.

Response :If swallowed: Call a poison control center or doctor. Rinse mouth. If on skin: Wash with plenty

of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse eyes cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical advice. Get medical attention if

you feel unwell.

Storage : Store locked up.

Disposal : Contact local sewer, municipal, state and/or federal agencies to determine appropriate

disposal options for the product. Dispose of this container with a registered reconditioner or

as otherwise appropriate.

Section 3 - Composition/Information on Ingredients

3.1 Substance details

| Dangerous components | CAS# | %Weight |
|----------------------|-------------|---------|
| Ethylene Glycol | 107-21-1 | 95% |
| Water | 7732-18-5 | 2.5% |
| Inhibitors & Dye | Proprietary | 2.5% |

Section 4 – First aid Measures

4.1 First aid measures

Skin:

Acute : Irritation of affected area with symptoms of reddening, itching, swelling, burning, possible

permanent damage, nausea, vomiting, weakness, and death.

Delayed: Irritation of affected area with symptoms of reddening, itching, swelling, burning, possible

permanent damage, nausea, vomiting, weakness, abdominal pain, muscle tenderness,

respiratory failure, severe metabolic acidosis, hypocalcemictetany and death.

Irritation may result. May be harmful if absorbed through skin.

Eye Contact: Irritation may cause transitory stinging and tearing.

Ingestion: Toxic may be harmful or fatal if swallowed.

4.2 First Aid Instructions

Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if

victim is not breathing. Seek medical attention.

Skin: Wash skin with soap and water for at least 20 minutes. Remove any contaminated clothing.

Seek medical attention immediately if symptoms or irritation develops.

Eye : Contact Flush with water for at least 20 minutes. Seek medical attention if irritation develops

or persists.

Ingestion : DO NOT induce vomiting, seek medical attention immediately. Do not give anything by mouth

to an unconscious person. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. Vomiting may occur spontaneously. If vomiting occurs and the victim is

conscious, give water to victim to further dilute the chemical.

Other : Consult a physician. Show safety data sheet to the doctor in attendance.

Section 5 – Fire Fighting

5.1 Extinguishing Media

Suitable extinguishing agents: Water, water fog, water spray, alcohol foam, dry chemical or carbon dioxide.

Smoke may contain the original material in addition to but not limited to: Carbon Monoxide, Carbon Dioxide.

5.2 Firefighters Advice

Protective equipment

: Wear self-contained breathing apparatus and protective suit. Evacuate personnel to safe areas and keep upwind of fire.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

General Measures

: Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Usage of safety glasses or goggles is recommended. Chemical resistant gloves, chemical resistant apron, boots, and full suit will be necessary depending on the extent of clean up task. If ventilation does not control airborne concentration then respiratory protection equipment that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements should be used.

6.2 Materials & Methods to Contain and Cleanup

Reference to other sections

: Collect liquid in an appropriate container or absorb with inert material and place in

chemical waste container.

Containment and Cleanup

: Do not flush to sewer. Comply with all federal, state, and local regulations.

Section 7 - Handling & Storage

7.1 Safe Handling

Precautions

: Protect container from physical damage. Wear appropriate personal protection equipment. Do not expose containers to open flame, excessive heat, or direct sunlight. Use local exhaust over processing area. Do not eat, drink or smoke around products.

7.2 Safe Storage

Storage and receptacles

: Store in a cool, dry and ventilated area away from sources of heat, moisture and incompatible materials. Observe all warnings and precautions listed for the product. Keep container closed to prevent contamination

Section 8 - Exposure Control

| OSHA Permissible Exposure Limits (PELs) | Not Applicable |
|--|--|
| American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values | ACGIH TLV: 100 mg/m3 |
| Other Exposure Limits | OSHA – Table Z-1 Limits for air contaminants - 1910.1000: 50 ppm 125 mg/m3 . |
| Engineering Control | Use mechanical (general) ventilation to control airborne levels Below exposure guidelines. |
| Individual Protection Measures | Wear protective safety glasses or goggles, gloves, apron, Vapor Respirator. |

Section 9 - Physical & Chemical Properties

9.1 Information On Basic Physical and Chemical Properties

| General Information | | |
|---|---|--|
| Appearance: | Liquid, Clear, Green | |
| Upper/lower flammability or explosive limits: | Not Explosive; LOWER: 3.2% (v) UPPER: 15.3% (v) | |
| Odor | Slight to no odor | |
| Vapor pressure: | 134 Pa / 0.1 mmHg | |
| Odor threshold: | No data available | |
| Vapor density (air = 1): | 2.14 | |
| pH: | 7.5 - 9.0 | |
| Relative density: | 1.120 - 1.140 | |
| Freezing point (as 50%) | -34℉ / -37℃ | |
| Solubility(ies) | Miscible in water | |
| Initial boiling point and boiling range | 385年 / 196℃ | |
| Flash point | 232年 / 111℃ | |
| Evaporation rate (Butyl Acetate = 1) | <1 | |
| Flammability (solid, gas) | This material is Not Flammable but can burn if heated | |
| Partition coefficient: n-octanol/water | Log Pow: -1.36 | |
| Auto-ignition temperature | > 700 F / > 370 ℃ | |
| Decomposition temperature | Not Applicable | |
| Viscosity | ~16 cps at 60F | |

Section 10 - Stability & Reactivity

Conditions to Avoid

Incompatible Materials

Reactivity : Product is stable under typical use temperatures. Chemical Stability : Product is stable under typical use temperatures. **Hazardous Reactions** : Avoid contact with oxidizing materials strong bases and strong acids.

: Heat, flames, ignition sources and incompatibles.

: Avoid contact with oxidizing agents, strong bases and strong acids.

Decomposition Products : Carbon dioxide and carbon monoxide may form when heated to decomposition.

Section 11- Toxicological Information

11.1 Effects from short term exposure

Delayed Effects : Irritation of affected area **Immediate Effects** : Irritation of affected area

Chronic Effects : Not Applicable

The numerical measures of toxicity (e.g., acute toxicity estimates such as the LD50 toxicity estimates such as the LD50 (median lethal dose)

: The estimated amount [of a substance] expected to kill 50% of test animals in a single dose.

Description of the symptoms

: This description includes the symptoms associated with exposure to the chemical including symptoms from the lowest to the most severe exposure.

Listed in the National Toxicology Program

Report on Carcinogens

Found to be a potential carcinogen in the **International Agency for Research on Cancer**

Monographs

Found to be a potential carcinogen by OSHA

: No

: No

: No

11.2 Effects from long term exposure

Delayed Effects : Irritation of affected area Immediate Effects : Irritation of affected area **Chronic Effects** : Teratogenic effects

The numerical measures of toxicity : Skin: LD50 - Rabbits - >10600 mg/kg Ingestion: LD50 - Rats - 7712 mg/kg;

Lethal Dose Human Adult - 90mL.

Description of the symptoms : Irritation, nausea, vomiting, abdominal pain, weakness, muscle tenderness,

respiratory failure, convulsions, cardiovascular collapse, pulmonary edema,

hypocalcemictetany, metabolic acidosis, death.

Listed in the National Toxicology Program

Report on Carcinogens

Found to be a potential carcinogen in the International Agency for Research on Cancer

Monographs

Found to be a potential carcinogen by OSHA

: No

: No

Section 12 - Ecological Information

Ecotoxicity : Low Ecotoxicity Persistence and Degradability : Biodegradable.

: Does not bioaccumulate significantly Bioaccumulation

: Dissolves in water. If product enters soil, it will be highly mobile and may Mobility in Soil

contaminate ground water.

: No Data Available Other Adverse Effects

Section 13 - **Disposal Considerations**

13.1 Waste treatment

Do not dump into sewers, on ground or into any bodies of water. Contact local sewer, municipal, state and/or federal agencies to determine appropriate disposal options

Section – 14 Transportation Information

Is product DOT regulated in Non-Bulk packaging?

| UN number | UN3082 |
|---|---|
| UN proper shipping name | Environmentally hazardous substances, liquid, n.o.s |
| Transport hazard class(es) | 9 |
| Packing group number | III |
| Environmental hazards (e.g., identify if it is a marine pollutant according to the International Maritime Dangerous Goods Code (IMDG Code)) | Not Regulated |
| Guidance on transport in bulk (according to Annex II of MARPOL 73/783 and the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (International Bulk Chemical Code (IBC Code)) | |
| Any special precautions which an employee should be aware of or needs to comply with, in connection with transport or conveyance either within or outside their premises. | |

: No

Section 15 - Regulatory Information

Safety Regulations

:OSHA Hazard Communication Standard: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

| SARA 311/312 | Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312 | Superfund Amendments and Reauthorization Act of 1986 Title III (SARA) Sections 311 and 312: Immediate (Acute) Health Hazard - Yes; Delayed (Chronic) Health Hazard - Yes; Fire Hazard - No; Reactive Hazard - No; Sudden Release of Pressure Hazard - No. Section 313: Product contains the following substances which are subject to reporting requirements and are listed in 40 CFR 372 - Component: Ethylene Glycol CAS#: 107-21-1 Amount: >=99.0% |
|---|--|---|
| HMIS | Blue/Health Red/Flammability Orange/Physical Hazard White/Personal Protection | 2 1 0 X |
| NFPA 0(no hazard) to 4(severe risk) | Health (Blue) Flammability (Red) Special (White) Instability/Reactivity (Yellow) | 2 1 0 N\A |
| US Toxic Substance Control Act CEPA – Domestic Substances List (DSL) | | All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30 All substances contained in this product are listed on the |
| | | Canadian Domestic Substances List (DSL) or are not required to be listed. |

Section 16 - Other Information

This SDS is applicable for all dilutions and containers for this brand of product. The information herein is provided in good faith and believed to be accurate as of the effective revision date shown. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/ user's responsibility to ensure that activities comply with all federal, state, provincial or local law.