

# DAVID WEBER OIL CO.

601 Industrial Road - Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax www.weberoil.com

Section 1 - Identification

1.1 Product Identifiers

1.4 Supplier Information

Product Name : WATER SOLUBLE OIL

1.2 Product usage

Recommended Usage : Soluble Oil

**Restricted Usage** : Not intended for any other usage

David Weber Oil Company

601 Industrial Road Carlstadt, NJ 07072

Phone: 201-438-7333
Fax: 201-438-3178

Email: sales@weberoil.com

1.3 Emergency support

**Emergency Support** : CHEMTREC

United States +1(800) 424-9300 International +01(703) 527-3887

Section 2- Composition/Information on Ingredients

## 2.1 Classification of Substance Mixture

GHS Rating(s) : H320 Eye Damage Category 2B

Signal Word : Not Applicable

2.2 Label Elements

No classified Hazards

Precautionary: P201 Obtain Special Instructions Before Use

Storage: P505 Dispose Of Container According To Regional Regulations

**Disposal:** P281 Use Personal Protective Equipment as required.

2.3 Other Hazards

Hazards not otherwise Classified (HNOC)

: Avoid prolonged or repeated contact with motor oil. Use of good hygiene practices will reduce the likelihood of potential health effects. When exposed wash areas with soap and water and

lauder contamined clothing.

## Section 3 - Hazards Identification

#### 3.1 Substance details

Chemical Name	CAS#	%Weight
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-53-6 11.0	64742-53-6	11.0
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC 64742-55-8 3.0	64742-55-8	3.0
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC 64742-56-9 2.0	64742-56-9	2.0
DISTILLATES, PETROLEUM, HYDROTREATED HEAVY NAPHTHENIC 64742-52-5 84.0	64742-52-5	84.0

Products containing mineral oil with less than 3% DMSO extract as measured by IP-346.

## Section 4 – First aid Measures

## 4.1 First aid measures

Eye Contact : Immediately flush eyes with plenty of water occasionally lifting the upper and lower eyelids.

Check and remove any contact lenses. Continue to rinse for at least 20 minutes. Get Medical

Attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing

is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth resuscitation.

Maintain an open airway. Get medical attention if symptoms occur.

ingestion : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be

give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by

mouth to an unconscious person. get medical attention if symptoms occur.

## 4.2 Symptoms & Effects

**To Physician**: Treat symptomatically. Contact poison specialist if product has been ingested.

**Specific Treatment**: No specific Treatment.

#### 4.3 Medical attention

Protection of first Aiders: No action should be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Note to Doctor : Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of

stomach contents is necessary, use method least likely to cause aspiration.

## ection 5 – Fire Fighting

## 5.1 Extinguishing Media

## Suitable Media Unsuitable Media

: CO2, Dry chemical, or Foam. Water can be used to cool and protect product. Do not use water jet as an extinguisher, it will spread the fire.

## Specific hazards Arising from this product

: When heated, hazardous gases may be released including: sulfur dioxide. A solid stream of water will spread the burning material. Material creates a special hazard because it floats on water this material creates a special hazard because it floats on water. This material is harmful to aquatic life. Any fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

## 5.2 Firefighters Advice

## Special protective equipment

: Fire Equipment Information: Fire-fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6 - Accidental Release Measures

## 6.1 Personal precautions, protective equipment

#### General Measures

: No health affects expect from the cleanup of this material if contact can be avoided. Follow personal protect equipment recommendations found in section 8 of this SDS.

## **6.2 Environmental Precautions**

Non-Emergency Personnel: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform authorities if the product has caused environmental pollution Water Polluting Material may be harmful to the environment if released in large quantities.

## 6.3 Materials & Methods to Contain and Cleanup

#### Reference Section 8

: Follow all protective equipment recommendations provided in Section 8.

#### Spill Control Measures

: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

Containment and Cleanup: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via licensed was disposal contractor. Contaminated absorbent material may pose the same threat hazard as the spilled product.

## Section 7 - Handling & Storage

## 7.1 Safe Handling

# Personal Protective Equipment

: Put on appropriate personal protective equipment (see section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, keep lid tightly closed when not in use. Empty containers that retain product residue and can be hazardous. Do not reuse container.

## 7.2 Safe Storage

#### Required conditions

: Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. Store away from incompatible materials. See section 10 for incompatible materials.

## 7.3 Specific End Use

## **Designed Purpose**

: This product is designed for use as a Soluble Oil

## Section 8 - Exposure Control

8.1 United S CAS	tates Exposure Limits Chemical Name	Exposure Limits	Source
64742-52-5	Distillates, petroleum, hydro treated heavy naphthenic	5mg/m3	IUCLID
64742-53-6	Distillates, petroleum, hydro treated light naphthenic	5mg/m3	IUCLID
64742-55-8	Distillates, petroleum, hydro treated light paraffinic	5mg/m3	NLM_CI
64742-56-9	Distillates, petroleum, solvent-dewaxed light paraffinic	5mg/m3	IPUCLID

#### **8.2 Exposure Controls**

#### **Engineering Controls**

: Material should be handled in enclosed vessels and equipment, in which case general room ventilation should be sufficient. Local exhaust ventilation should be used at points where dust, mist, vapors or gases can escape into the room air. No special requirements under ordinary conditions of use and with adequate ventilation.

## Environmental Exposure Control Hygiene Measures

: General room ventilation should be satisfactory. Local exhaust ventilation may be necessary if misting is generated.

Eye / Face Protection Skin / Hand Protection : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

: If contact is likely, safety glasses with side shields are recommended.

: Butyl rubber. Use nitrile or neoprene gloves. Use good industrial hygiene practices. In case of skin contact, wash hands and arms with soap and water. Use caution when opening manway covers of storage and transportation containers. 3-nitroaniline crystals may be present on the interior surface of these openings. 3-nitroaniline is toxic by dermal exposure.

#### **Respiratory Protection**

: Use a properly fitted air purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this a necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9 - Physical & Chemical Properties

## 9.1 Information On Basic Physical and Chemical Properties

Physical state : Liquid
Color : B&C

Odor : Characteristic of Petroleum

Odor threshold: No Data AvailablepH: No Data AvailableFreezing Point: No Data AvailableBoiling Point / Range: No Data Available

Flash Point COC :221C

Evaporation rate:

Upper Explosive Limits (% air)

Lower Explosive Limits (% air)

Flammability (solid, gas)

Vapor pressure

Vapor density (air=1)

Relative Density

: No Data Available
: No Data Available
: Not Applicable
: <1 mm Hg
: >1
: >1
: >1
: >1
: >1

Auto-ignition temperature: Not DeterminedDecomposition temperature: Not Determined

Solubility in water : Soluble

Partition coefficient, n-octanol/water : No Data Available

## Section 10 - Stability & Reactivity

## 10.1 Material Analysis

**Reactivity** : No Data Available.

Chemical stability: Stable Under Normal Circumstances.Possibility of hazardous reactions: Hazardous polymerization will not occur.

## 10.2 Environmental

Conditions to avoid : Temperatures above the high flash point of this combustible material in

combination with sparks, open flames, or other sources of ignition. Moisture

(will lead to product performance degradation).

Incompatible materials : Strong oxidizing agents.

Hazardous decomposition products :Carbon monoxide, smoke carbon monoxide, sulfur oxides, aldehydes, and other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium,

sodium, and hydrogen sulfide may also be present.

## **Section 11- Toxicological Information**

## 11.1 Toxicological Effects

**Ingestion Toxicity**: No hazard in normal industrial use.

**Skin Contact** : This material is likely to be slightly irritating to skin based on animal data.

Can cause minor skin irritation, defatting, and dermatitis. Likely to be

practically non-toxic based on animal data.

**Inhalation Toxicity** : Non-hazardous under Respiratory sensitization category.

Eye Contact : The material is likely to be moderately irritating to eyes based on animal

data. No hazard in normal industrial use.

## Section 11- **Toxicological Information**

## 11.1 Toxicological Effects

**Ingestion Toxicity**: No hazard with normal usage.

**Skin Contact**Inhalation Toxicity

This material is likely to be slightly irritating to skin based on animal data.

The material is likely to be irritating to eyes based on animal data.

**Eye Contact**: Non-hazardous under Respiratory Sensitization category.

## 11.2 Inhalation Toxicity Data

CAS	Chemical Name	Test	Value	Species	Source
64742-55-8	8 Distillates, petroleum, hydro treated light paraffinic	Inhalation	3900mg/m3 4h	Rat	NLM_CIP

## 11.3 Dermal & Other Toxicity Data

CAS	Chemical Name	Test	Value	Species	Source
64742-52-5	Distillates, petroleum, hydrotreated heavy naphthenic	LC50	5000mg/L96h	Oncorhynchus	IUCLID
64742-53-6	Distillates, petroleum, hydrotreated light naphthenic	LC50	5000mg/L96h	Oncorhynchus	IUCLID
64742-55-8	Distillates, petroleum, hydrotreated light paraffinic	LC50	5000mg/L96h	Oncorhynchus	IUCLID
64742-56-9	Distillates, petroleum, solvent-dewaxed light paraffinic	LC50	5000mg/L96h	Oncorhynchus	IUCLID

Sensitizer : No data available to indicate product or components may be a skin sensitizer.

Mutagenicy : No data available to indicate product or any components present at greater

than 0.1% is mutagenic or genotoxic.

**Carcinogenity** : Not expected to cause cancer. This product meets the IP-346 criteria of <3%. : No data available if components greater than 0.1% may cause birth defects.

## Section 12 - Ecological Information

## 12.1 Aquatic Toxicity

Acute Aquatic ecotoxicity : Non-hazardous under Aquatic Acute Environment category. Chronic Aquatic ecotoxicity : Non-hazardous under Aquatic Chronic Environment category.

Persistence and degradability : Biodegrades slowly.

Bioaccumulative potential : Bioconcentration may occur.

**Mobility in soil**: This material is expected to have essentially no mobility in soil.

Results of PBT and vPvB assessment : Not determined.

Other adverse effects : No data available.

## 12.2 Ecological data

CAS	Chemical Name	Test	Value	Species	Source
64742-52-5	Distillates, petroleum, hydrotreated heavy naphthenic	EC50	1000mg/L 48h	Daphnia magna	IUCLID
64742-53-6	Distillates, petroleum, hydrotreated light naphthenic	EC50	1000mg/L 48h	Daphnia magna	IUCLID
64742-55-8	Distillates, petroleum, hydrotreated light paraffinic	EC50	1000mg/L 48h	Daphnia magna	IUCLID
64742-56-9	Distillates, petroleum, solvent-dewaxed light paraffinic	EC50	1000mg/L 48h	Daphnia magna	IUCLID

## Section 13 - Disposal Considerations

#### 13.1 Waste treatment

Waste treatment methods

Disposal Methods Waste Disposal : Dispose of according to Federal, State, Local, or Provincial regulations.

: Recycle used oil.

: Spent or discarded material is non-hazardous according to environmental

regulations.

**Contaminated packaging**: Recycle containers whenever possible!

## **Section – 14 Transportation Information**

## 14.1 U.S. Department of Transportation (DOT)

**Shipping Description**: If shipped by land in a packaging having a capacity of 3,500 gallons or more,

the provisions of 49 CFR, Part 130 apply. (Contains oil) International Maritime

Dangerous Goods (IMDG)

**DOT Compliance Note** : U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 25.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable International Civil Aviation Org. / International Air Transport Assoc.

(ICAO/IATA)

**DOT Compliance Requirement**: U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 24

Section	15 -	Regulatory	<b>Information</b>

Regulatory Agency		Chemical List Status
(TSCA) Toxic	SCA) Toxic : All components are either listed or not regulated US TSCA Inventory.	
WHMIS Hazard Class	: None	
Canada CPR	: This product has been classified in accordance with the hazard criteria Con Regulations (CPR) and the SDS contains all the information required by the	
CERCLA Sections 302, 313, 372 311, 312	: This material does not contain reportable chemicals. : Acute Health Hazard No Pressure Hazard No Fire Hazard No Chronic Health Hazard No Reactive Hazard No	
New Jersey Right to Know (NJ RTK)	: This material does not contain reportable chemicals.	
Massachusetts Right to Know (MA RTK)	: This material does not contain reportable chemicals.	64742-53-6 64742-55-8 64742-56-9
Pennsylvania Right to Know (PA RTK)	: This material does not contain reportable chemicals.	
Rhode Island Right to Know (RI RTK)	: This material does not contain reportable chemicals.	

## Section 16 - Other Information

**ACGIH** American Conference of Governmental Industrial Hygienists NFPA: HEALTH Code of Federal Regulations CFR FLAMMABILITY United States Department of Transportation DOT INSTABILITY 0 **SPECIAL** 

**GHS** Globally Harmonized System of Classification and Labeling of Chemicals

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RTK Right-to-Know

Short-term Exposure Limit SARA **TSCA** Toxic Substances Control Act

WHMIS Workplace Hazardous Materials Information System



Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness.

Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.