



PRODUCT DATA SHEET

DAVID WEBER OIL CO.

601 Industrial Road · Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax

www.weberoil.com

UNIVERSAL TRACTOR FLUID

Universal Tractor Fluid represents a new generation in hydraulic/power transmission fluid performance. This product provides outstanding service in gears, pumps, differentials, final drives, bearings, wet brakes, transmissions and PTO (power takeoff) clutches.

Extensive research and thousands of hours of grueling field tests have demonstrated that Universal Tractor Fluid exceeds OEM manufacturers' standards for wear, chatter, brake capacity, PTO performance and filterability.

Summary of Universal Tractor Fluid Performance Data

Tractor Testing

TRACTOR OEMs

AGCO:

AGCO Allis

Power Fluid 821XL

ACGO-Chalmers

Power Fluid 821

Deutz-Allis

272843, 257541, 246634

Massey-Ferguson

M-1135, M-1141, M-1145,
M-1143, M-1129A, M-1110,
M-1127A, M-1127B

White Farm

Q-1826

Minneapolis-Moline

Q-1766, Q-1722, Q-1766B

Oliver

Q-1705

New Idea

Q-1802, Type 55

ZF

TE-ML 03E, TE-ML 03F

TE-ML 05F, 05E, TE-ML 06K

*Consult Tech Services

CNH Global N.V.:

Case International

MS-1206, MS 1207 (Hy-Tran Plus)

CNH MS-1209*

Case-IH

MS-1210 / JIC 145 (TCH)

Jl Case

JIC 143 / 144

International Farmall

MS-1204, JIC 185

International Harvester

B-5, B-6

Steiger

SENS 17001

New Holland (Fiat)

Ford and New Holland

MAT 3525, FNHA-2-C-201

MAT 3526

FNHA-2-C-200

FNHA-2-C-200A

ESN-M2C41-B, M2C43,

M2C48-A, M2C48-B,

M2C53-A, M2C53-B, M2C92-A

M2C134-A, B, C, D (current)

35VQ25, M-2952-S (Vickers)

Kubota

UDT

Sperry-Vickers

I-286-S (Vickers)

M-2950-S (Vickers)

Versatile

Specification 23M or 24M

Hesston-Fiat (tractors only):

AF-87, Multi-F, Multi-G

Volvo CE

WB 101

John Deere

JDM J20C (Hygard)

JDM J20A, J20B, J14B, J14C

JDM J21A, JDT 303, Quatrol

Komatsu Dresser

B-06-0001, B-06-0002

Renk Dromat

873, 874 A, 874 B

TRANSMISSION OEMs:

Caterpillar TO-2

Allison C-2, C-3

Typical Properties

SAE Grade	Result
Viscosity, cSt @ 40°C	57.5
Viscosity, cSt @ 100°C	9.25
Viscosity, cP @ -20°C	2600
Viscosity, cP @ -35°C	20,500
Viscosity Index	155
Pour point, °F	-44
Flash Point, °F	432
Sulfated Ash, wt%	1.48
Zinc, wt%	0.157