

## PRODUCT DATA SHEET

DAVID WEBER OIL CO.

601 Industrial Road · Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax  
www.weberoil.com

# Gibraltar DEXRON III/MERCON ATF


Premium ATF for pre-2005 GM/Ford vehicles

**Gibraltar DEXRON III/MERCON ATF** is a premium automatic transmission fluid designed for electronically controlled transmissions in pre-2005 GM and Ford cars and light-duty vehicles. It is suitable for use in Allison C-4 and TES-389™ applications due to its superior characteristics and commonly used for hydraulic or power steering fluid\*.

**Gibraltar DEXRON III/MERCON ATF** utilizes high quality, highly refined base stocks for long service life and a superior additive system for protection of key transmission components. It contains specially formulated antioxidants and anti-wear agents, detergents, and de-foaming agents, as well as special friction modifiers and lubricity agents for smooth shifting over a wide range of driving conditions, temperatures, and transmissions designs.

**Gibraltar DEXRON III/MERCON ATF** has the following benefits:

- Superior quality base oil for lasting service life
- Excellent anti-wear and anti-shudder performance
- High lubricity for smoother shifts
- Excellent torque profile
- Ideal for service fill applications



## PRODUCT DATA SHEET

# DAVID WEBER OIL CO.

601 Industrial Road · Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax  
www.weberoil.com

### APPLICATION RECOMMENDATIONS

1974-2005 GM vehicles specifying DEXRON®, DEXRON®-II, or DEXRON®-III

1988-1997 Ford and other vehicles requiring MERCON®

1981 and later Ford vehicles requiring an M2C138CJ or M2C166H fluid

Allison C-4, TES-389™

### TYPICAL PROPERTIES

Color	Red
Viscosity, cSt @ 100 °C	7.46
Viscosity, cSt @ 40 °C	37.1
Viscosity Index	190
Flash Point, COC, °C, min.	224
Pour Point, °C, max.	-41
Rust Test	Pass
Copper Strip Test	1a

\*Always consult owner's manual for fluid recommendations.