

PRODUCT DATA SHEET

DAVID WEBER OIL CO.

601 Industrial Road • Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax
www.weberoil.com

Gibraltar CAT TO-4 Fluid


Heavy-Duty TransFluids

Gibraltar CAT TO-4 Fluids are premium transfluids that are designed using the latest technology. These lubricants are formulated to meet the stringent requirements of today's complex power transmissions, wet-disc brakes, hydraulic systems, and final drive units.

Gibraltar CAT TO-4 Fluids incorporate select frictional modifiers and anti-wear agents to provide superior performance and seal compatibility. They exceed the capabilities of mixed fleet engine oils and some off-road hydraulic fluids and are specifically formulated to exceed Caterpillar's TO-4 requirements. **Gibraltar CAT TO-4 Fluids** are built to withstand severe service duty and give long service life.

Gibraltar CAT TO-4 Fluids have the following benefits:

- Controlled Frictional Performance
- Elimination of Clutch Slippage and Chatter
- Excellent Low-Temp Pumpability
- Oxidatively Stable and Corrosion Protection
- Shear Stable and High Levels of Anti-wear Protection



PRODUCT DATA SHEET

DAVID WEBER OIL CO.

601 Industrial Road • Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax
www.weberoil.com

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

SAE 0W-20

ACEA: C5

API: SN/SN Plus

Porche: C20

VW: 508.00/509.00, TL 52577

SAE 0W-30

ACEA: C3

BMW: LL-04

MB: 229.31, 229.51, 229.52

Porche: C30

VW: 504/507, TL 52545

TYPICAL PROPERTIES

SAE GRADE	0W-20	0W-30
Appearance	Blue/Green	Amber
Viscosity, cSt @ 100°C	8.2	12.0
Viscosity, cP, -30° C	6,300	5,900
Sulfated Ash, wt./%	0.8	0.7
HTHS, cP @ 150°C	2.7	3.5
NOACK, wt./%	10.0	10.0
TBN	9.3	8.1