

PRODUCT DATA SHEET

DAVID WEBER OIL CO.

601 Industrial Road • Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax
www.weberoil.com

Gibraltar Universal Tractor Fluid


Multi-functional Anti-Wear Hydraulic Fluid

Gibraltar Universal Tractor Hydraulic Fluid is a high-performance anti-wear lubricant designed for high pressure hydraulic systems, hydrostatic transmissions, power-takeoff units, and wet brakes and clutches often found in common-sump systems. It provides outstanding service and protection to gears, pumps, differentials, final drives, bearings, clutches, and other severe service systems.

Gibraltar Universal Tractor Hydraulic Fluid exceeds OEM standards for wear, chatter, braking capability and filterability. It provides outstanding protection from rust, has good demulsibility and air release properties and excellent low-flow properties. Designed for modern hydraulic systems and power transmission applications, **Gibraltar Universal Tractor Hydraulic Fluid** is suitable for applications beyond OEM recommendations.

Gibraltar Universal Tractor Hydraulic Fluid has the following benefits:

- PTO Wear and Chatter Control
- Shear Stable, High Viscosity Index
- Excellent Thermal and Oxidative Stability
- Wear Protection for Transmissions, Clutches and Drives
- Superior Hydraulic and Power Steering Performance



PRODUCT DATA SHEET

DAVID WEBER OIL CO.

601 Industrial Road • Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438.3178 fax
www.weberoil.com

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

API GL-4 • Allison Type C-4 • AGCO Power Fluid 821 XL
• Case IH MS1210, MS1209, MS1207, MS1206, MS
1204-07/09 • Case New Holland (CNH) MAT-3509,
3525, 3506, 3505 • Caterpillar TO-2 • Dennison HF-0,
HF-1, HF-2 • Fendt • Ford ESN M2C134-A/B/C/D,
FNHA-2C-201.00, FNHA-2-C-200.00, M2C86-B/C,
M2C41-B, M2C48-A/B • International Harvester B-6 Hy-
Tran • John Deere J14B/C, J20A/B, J20C (Hygard), J21A

Kubota UDT Fluids • Massey Ferguson M1110,
M1127B, M1129A, M1143, M1141 (Permatran III) •
Minneapolis-Moline 35154, 35202, 35301 • Sauer-
Sundstrand Hydrostatic Transmission Fluid • VALTRA
G2-08 • VCE (Volvo) WB 101 • Vickers M-2950-S, I-
286-S, 35VQ25 • White Farm Equipment Q-1705, Q-
1722, Q-1766B, Q-1802 (Type 55 Fluid), Q-1826
(HTF) • ZF TE-ML 03E/05F/06E/06F/06K/17E/21F

TYPICAL PROPERTIES

SAE Viscosity Grade	10W-30
Viscosity, cSt @ 100 °C	9.2
Viscosity, cSt @ 40 °C	57.5
Viscosity, cP @ -20 °C	2,600
Viscosity, cP @ -35 °C	20,500
Viscosity Index	155
Flash Point, COC, °C (F), min.	222 (432)
Pour Point, °C (F), max.	-42 (-44)
Sulfated Ash, wt.%	1.48
Zinc, wt.%	0.1570