DAVID WEBER OIL CO.
601 Industrial Road • Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438. 3178 fax
www.weberoil.com

PRODUCT DATA SHEET

# Gibraltar Straight Mineral Gear Lube

## High Quality API GL-1 Gear Oils

**Gibraltar Straight Mineral Gear Lubes** are premium quality gear oils for use in manual transmissions, differentials, manual steering boxes, universal joints and other automotive units that do not require extreme pressure gear lubricants.

**Gibraltar Straight Mineral Gear Lubes** offer a unique combination of system cleanliness, lubricity and good inherent demulsibility. Their superior protection under all operating conditions helps avoid downtime and prevent excessive or premature wear. **Gibraltar Straight Mineral Gear Lubes** meet the API requirements for GL-1 classification.

**Gibraltar Straight Mineral Gear Lubes** offer the following benefits:

- **High lubricity and wear protection**
- **Excellent thermal and oxidative stability**
- **Good water and foam separability**
- **Suitable for multiple automotive applications**
- **Thermally and oxidatively stable**

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. The information contained herein is subject to change without notice. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation.

DAVID WEBER OIL CO.
601 Industrial Road • Carlstadt, NJ 07072 | 201.438.7333 phone | 201.438. 3178 fax
www.weberoil.com

GIBRALTAR Industrial Lubricants

# PRODUCT DATA SHEET

## SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

API GL-1

| TYPICAL PROPERTIES | | |
|---|---|---|
| SAE Viscosity Grade | 90 | 140 |
| API Service | GL-1 | GL-1 |
| Specific Gravity | .896 | .896 |
| Viscosity, cSt @ 100°C | 17.6 | 28.54 |
| Viscosity Index | 100 | 95 |
| Flash Point, COC, °F, min. | 400 | 560 |
| Pour Point °C, max. | -18 | 0 |

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. The information contained herein is subject to change without notice. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation.