



SAFETY DATA SHEET

Section 1 – Identification

1.1 Product identifier

Product Name : Gibraltar Transmaxx ATF

1.2 Product usage

Recommended Usage : Automatic Transmission Fluid

1.3 Emergency support

Emergency Support : CHEMTREC
United States +1(800) 424-9300
International +01(703) 527-3887

1.4 Supplier Information

David Weber Oil Co.
601 Industrial Road
Carlstadt, NJ 07072
Manufactured By David Weber Oil Co.

Section 2- Hazards Identification

2.1 Classification of the Substance of Mixture

GHS Rating(s) : No classified hazards
Signal Word : Not applicable

2.2 Label Elements

Precautionary : Obtain special instructions before use.
: Do not handle until all safety precautions are understood.
: Use personal protective equipment as required
Response : If exposed or concerned: get medical advice/attention
Storage : Store locked up
Disposal : Dispose of container according to regional regulations.

Section 3 - Composition/ Information on Ingredients

3.1 Substance details

| Chemical Name | CAS # | % Weight |
|--|------------|----------|
| ACC # 251617 | RR-43084-2 | 18.0 |
| Lubricant base oil (Petroleum) | 64742-54-7 | 40.0 |
| Distillates (Petroleum), Hydrotreated light paraffinic | 64742-55-8 | 40.0 |
| Distillates (Petroleum), Hydrotreated light | 64742-53-6 | 2.0 |

Products containing mineral oil with less than 3% DMSO extract as measured by IP-346

Section 4 – First aid Measures

4.1 First aid measures

| | |
|---------------------------|---|
| Eye | : Immediately flush eyes with plenty of water occasionally lifting the upper and lower eye lids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth resuscitation. Maintain an open airway. Get medical attention if symptoms occur. |
| Ingestion Symptoms | : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. get medical attention if symptoms occur. |

4.2 Symptoms & Effects

| | |
|---------------------------|---|
| Note to Physicians | : Treat symptomatically. Contact poison specialist product has been ingested. |
| Specific Treatment | : No specific treatment. |

4.3 Medical Attention

| | |
|-----------------------------------|---|
| Protection of First Aiders | : No action should be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |
| Note to Doctor | : Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration. |

Section 5 – Fire Fighting

5.1 Extinguishing Media

**Suitable Media/
Unsuitable Media**

: CO2, Dry chemical, or Foam. Water can be used to cool and protect product. Do not use water jet as an extinguisher, it will spread the fire.

**Specific hazards arising from
this product**

: When heated, hazardous gases may be released including: sulfur dioxide. A solid stream of water will spread the burning material. Material creates a special hazard because it floats on water. This material creates a special hazard because it floats on water. This material is harmful to aquatic life. Any fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

5.2 Firefighters Advice

Special protective equipment

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face -piece operated in positive pressure mode.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment

General Measures

: No health affects expected from the cleanup of this material if contact can be avoided. Follow personal protective equipment recommendations found in section 8 of this SDS.

6.2 Environmental Precautions

Non-Emergency Personnel

: Avoid dispersal of spilled material and runoff and contact with soil , waterways, drains

6.3 Materials & Methods to Contain and Cleanup

and sewers. Inform authorities if the product has caused environmental pollution Water Polluting Material may be harmful to the environment if released in large quantities.

**Reference Section 8
Spill Control Measures**

: Follow all protective equipment recommendations provided in Section *
: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

Containment and Clean up

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages with noncombustible, absorbent material e.g. sand earth vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via licensed waste disposal contractor. Contaminated absorbent material may pose the same threat hazard as the spilled product.

Section 7 - Handling & Storage

7.1 Handling Procedures

Personal Protective Equipment : Put on appropriate personal protective equipment (see section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, keep lid tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

7.2 Storage

Required conditions : Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. Store away from incompatible materials. See section 10 for incompatible materials.

7.3 Specific End Use

Designed Purpose : This product is designed for use as a Specialized Usage Lube Oil

Section 8 - Exposure Control

8.1 United States Exposure Limits

| CAS | Chemical Name | Exposure Limits | Source |
|------------|---|--------------------|--------|
| 64742-53-6 | Distillates, petroleum, hydrotreated light naphthenic | 5mg/m ³ | IUCLID |
| 64742-54-7 | Distillates, petroleum, hydrotreated heavy paraffinic | 5mg/m ³ | IUCLID |
| 64742-55-8 | Distillates, petroleum, hydrotreated light paraffinic | 5mg/m ³ | NLM_CI |

8.2 Exposure Controls

| | |
|--|---|
| Engineering Controls | : Material should be handled in enclosed vessels and equipment, in which case general room ventilation should be sufficient. Local exhaust ventilation should be used at points where dust, mist, vapors or gases can escape into the room air. No special requirements under ordinary conditions of use and with adequate ventilation. |
| Environmental Exposure Controls | : General room ventilation should be satisfactory. Local exhaust ventilation may be necessary if misting is generated. |
| Hygiene Measures | : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. |
| Eye/Face Protection | : If contact is likely, safety glasses with side shields are recommended. |
| Skin/Hand Protection | : Butyl rubber, use nitrile or neoprene gloves. Use good industrial hygiene practices. In case of skin contact, wash hands and arms with soap and water. Use caution when opening manway covers of storage and transportation containers. 3-nitroaniline crystals may be present on the interior surface of these openings. 3-nitroaniline is toxic by dermal exposure. |
| Respiratory Protection | : Use a properly fitted air purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this a necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |

Section 9 - Physical & Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

| | |
|---|-------------------------------|
| Physical state | : Liquid |
| Color | : B&C |
| Odor | : Characteristic of Petroleum |
| Odor threshold | : No Data Available |
| pH | : No Data Available |
| Freezing Point | : No Data Available |
| Boiling Point / Range | : No Data Available |
| Flash Point COC | : 211C |
| Evaporation rate | : No Data Available |
| Upper Explosive Limits (% air) | : No Data Available |
| Lower Explosive Limits (% air) | : No Data Available |
| Flammability (solid, gas) | : Not Applicable |
| Vapor pressure | : <1 mm Hg |
| Vapor density (air=1) | : > 1 |
| Relative Density | : 0.85 |
| Auto-ignition temperature | : Not Determined |
| Decomposition temperature | : Not Determined |
| Solubility in water | : Negligible, 0-1% |
| Partition coefficient, n-octanol/water | : No Data Available |

Section 10 - Stability & Reactivity

| | |
|---|--|
| Reactivity | : No Data Available |
| Chemical Stability | : Stable under normal circumstances |
| Hazardous Reactions | : Hazardous polymerization will not occur. |
| Conditions to Avoid | : Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. |
| Incompatible Materials | : Strong oxidizing agents |
| Hazardous decomposition Products | : Carbon monoxide, Smoke, Carbon monoxide, sulfur oxides, aldehydes, and other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present |

Section 11- Toxicological Information

11.1 Toxicological Effects

| | |
|------------------------------|---|
| Ingestion toxicity | : No hazard with normal usage. |
| Skin Irritation | : This material is likely to be slightly irritating to skin based on animal data. |
| Inhalation toxicity | : No data available |
| Eye Irritation | : The material is likely to be irritation to eyes based on animal data. |
| Sensitizer | : No data available to indicate product or components may be a skin sensitizer. |
| Mutagenicity | : No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic. |
| Carcinogenicity | : Not expected to cause cancer. This product meets the IP-346 criteria. |
| Reproductive Toxicity | : No data available if components greater than 0.1% may cause birth defects. |

11.2 Inhalation Toxicity Data

| CAS | Chemical Name | Test | Value | Species | Source |
|------------|---|------------|-----------------------------|---------|---------|
| 64742-55-8 | Distillates, petroleum, hydrotreated light paraffinic | Inhalation | 3900.0 mg/m ³ 4h | Rat | NLM_CIP |

Section 12 - Ecological Information

12.1 Aquatic Toxicity

| | |
|---|--|
| Persistence & Degradability | : No Data Available |
| Bioaccumulation Potential | : Bioconcentration may occur. No Data Available. |
| Soil Mobility | : No Data Available. |
| Results of PBT and vPvB assessment | : Not determined |
| Other Adverse Effects | : No Data Available. |

12.2 LC50 Toxicity Data

| CAS | Chemical name | Test | Value | Species | Source |
|------------|---|------|----------------|--------------|--------|
| 64742-53-6 | Distillates, petroleum, hydrotreated light naphthenic | LC50 | 5000.0mg/L 96h | Oncorhynchus | IUCLID |
| 64742-54-7 | Distillates, petroleum, hydrotreated heavy paraffinic | LC50 | 5000.0mg/L 96h | Oncorhynchus | IUCLID |
| 64742-55-8 | Distillates, petroleum, hydrotreated light paraffinic | LC50 | 5000.0mg/L 96h | Oncorhynchus | IUCLID |

12.3 Other Toxicity Data

| CAS | Chemical name | Test | Value | Species | Source |
|------------|---|------|----------------|---------------|--------|
| 64742-53-6 | Distillates, petroleum, hydrotreated light naphthenic | EC50 | 1000.0mg/L 48h | Daphnia magna | IUCLID |
| 64742-54-7 | Distillates, petroleum, hydrotreated heavy paraffinic | EC50 | 1000.0mg/L 48h | Daphnia magna | IUCLID |
| 64742-55-8 | Distillates, petroleum, hydrotreated light paraffinic | EC50 | 1000.0mg/L 48h | Daphnia magna | IUCLID |

Section 13 - Disposal Considerations

13.1 Disposal Instructions

| | |
|--------------------------------|---|
| Waste treatment methods | : Dispose of according to Federal, State, Local, or Provincial regulations. |
| Disposal Methods | : Recycle used oil. |
| Waste Disposal | : Use material is non-hazardous according to environmental regulations. |
| Contaminated packaging | : Recycle containers whenever possible |

Section – 14 Transportation Information

14.1 U.S. Department of Transportation (DOT)


| | |
|-----------------------------------|---|
| Shipping description | : If shipped by land in a packaging having a capacity of 3,500 gallons or more, the provisions of 49 CFR, Part 130 apply. (Contains oil) International Maritime Dangerous Goods (IMDG) |
| DOT Compliance Note | : U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 25. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable International Civil Aviation Org. / International Air Transport Assoc.(ICAO/IATA) |
| DOT Compliance Requirement | : U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23, 24 |

Section 15 - Regulatory Information

| | | |
|--|---|---|
| Agency (TSCA) Toxic Substance Control Act | : All components are either listed or not regulated US TSCA Inventory | Inventory Status 64742-54-7 64742-55-8 64742-53-6 |
| WHMIS Hazard Class | : None | |
| Canada CPR | : This product has been classified in accordance with the hazard criteria Controlled products regulations (CPR) and the SDS contains all the Information required by the regulations. | |
| CERCLA Sections 302, 313, 372 311,312 | : This material does not contain reportable chemicals : Acute Health Hazard No Pressure Hazard No Chronic Health Hazard No Reactive Hazard No | Fire Hazard No |
| New Jersey Right To Know (NJ RTK) | : This material does not contain reportable chemicals | |
| Massachusetts Right To Know (MA RTK) | : This material contains the following listed chemicals | 64742-55-8 64742-53-6 |
| Pennsylvania Right To Know (PA RTK) | : This material does not contain reportable chemicals | |
| Rhode Island Right To Know (RI RTK) | : This material does not contain reportable chemicals | |

Section 16 - Other Information

| | | | |
|--------------|--|---------------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | NFPA Ratings | |
| CFR | Code of Federal Regulations | Health | 0 |
| DOT | United States Department of Transportation | Flammability | 1 |
| GHS | Globally Harmonized System of Classification and Labeling of Chemicals | Instability | 0 |
| NIOSH | National Institute for Occupational Safety and Health | Special | - |
| OSHA | Occupational Safety and Health Administration | | |
| PEL | Permissible Exposure Limit | | |
| RTK | Right-to-Know | | |
| SARA | Short-term Exposure Limit | | |
| TSCA | Toxic Substances Control Act | | |
| WHMIS | Workplace Hazardous Material Information System | | |



The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.